

MATERIAL SAFETY DATA SHEET

Section 1 Introductory and Company Details

Flexitech Pty Ltd ABN 84 060 559 846 Ph: 07 3879 3877
67 Boundary Road, Fax: 07 3879 4299
CAROLE PARK, BRISBANE,
AUSTRALIA 4300

This edition supersedes all previous editions.
Edition Date: 1st July 2006

Emergency telephone number 0418 560 223.
During normal business hours EST call 07 3879 3877.

**Not Classified as Hazardous
According to the Criteria of Worksafe Australia**

Section 2 Identification

PRODUCT NAME	"Primerlock"
OTHER NAMES:	None
U.N. No.	Non allocated
DANGEROUS GOODS CLASS:	Non allocated
SUBSIDIARY RISK:	Non allocated
HAZCHEM CODE:	Non allocated
POISON SCHEDULE:	Non scheduled
PRODUCT TYPE:	water based dispersion
RISK PHRASES:	Non allocated
SAFETY PHRASES:	Non allocated

MAJOR RECOMMENDED USE: Primer for cement tiles
RECOMMENDED METHOD
OF APPLICATION: Spray or Brush

PHYSICAL DESCRIPTION/PROPERTIES:
APPEARANCE & ODOUR: Milky white liquid with mild
acrylic odour
FLASH POINT: Not applicable
BOILING POINT: 100°C - Water
FLAMMABILITY LIMITS: UPPER: not applicable
LOWER: not applicable

VAPOUR PRESSURE
@ 760MM Hg @ 25°C: not known
SOLUBILITY IN WATER: miscible
pH: 9
Density: approx 1.03
OTHER DATA: none noted

INGREDIENTS:	CHEMICAL ENTITY	CAS No.	PROPORTION
	Water based acrylic emulsion refer Sect 4		> 50%
	Water		to 100%

No other Hazardous Materials are present in this product at concentrations above the cut off levels as noted in the list of Designated Hazardous Substances, NOHSC:10005 (1994), or as defined in the Approved Criteria For Classifying Hazardous Substances, NOHSC:1008 (1994).

Section 3 Health Hazard Information

HEALTH EFFECTS: ACUTE
SWALLOWED: May cause nausea and diarrhoea.
EYE: Abrasive Irritating to the eye.
SKIN: May cause skin irritation and dryness on repeated or prolonged skin contact.
INHALED: Some persons may find the odour causes headache and nausea

FIRST AID:
SWALLOWED: Do not induce vomiting. Give copious quantities of water and seek medical advice.
EYE: Flush with water for 15 minutes and consult a Doctor.

INHALED: Remove person to fresh air. If breathing stops apply artificial respiration and other First Aid techniques as required and obtain immediate medical assistance.

FACILITIES: No specific First Aid Facilities are required other than those required by relevant legislation such as, for example, the Occupational Health and Safety (First Aid) Regulation 1089 (NSW).

ADVICE
TO DOCTOR: Avoid aspiration risks if vomiting induced.
The polymeric component will form films on drying.

Section 4 Precautions for Use

EXPOSURE:
The acrylic emulsion may contain residual monomers, to a maximum of 0.5%. The exposure limits as set by NOHSC Australia are as follows:-
Butyl Acrylate CAS # 141-32-2 20 ppm TWA
Methacrylic Acid CAS # 79-41-4 50 ppm TWA
Methyl Methacrylate CAS # 80-62-6 10 ppm TWA

VENTILATION: Ensure adequate ventilation, sufficient to ensure exposure below published limits as noted above.
Forced ventilation is not normally required.

PERSONAL PROTECTION:
REPIRATORY TYPE (AS1716) An ORGANIC VAPOUR MASK if exposed to a mist, aerosol or vapours.
GLOVE TYPE: Neoprene.
EYE PROTECTION: Goggles or safety glasses.
CLOTHING: Sufficient to avoid skin contact.

Section 5 Handling

DANGEROUS GOODS
CLASS/SUBSIDIARY RISK: none allocated
EXPLOSION HAZARD: non flammable
TOXICOLOGICAL DATA: none noted
ECOLOGICAL DATA: none noted

The information given and the recommendations made herein apply to this product alone and not combined with any other product/s. Such are based on our research and on data from other reliable sources and are believed to be accurate. No guarantee of accuracy is made. It is the purchasers' responsibility before using this product to verify this data under their own operating conditions and to determine whether the product is suitable for their purposes.

END OF DOCUMENT